



Product Data Sheet 5303

General Product Description

	Min	Max	Target
%Ash	0	0.2	<input type="checkbox"/>
Iodine Adsorption#/kg	235	271	<input type="checkbox"/>
Tinting Strength	83	91	<input type="checkbox"/>
Dibutyl Phthalate Absorb	182	202	<input type="checkbox"/>
Powdered Carbon Black			<input type="checkbox"/>

Type: CARBON BLACK POWDER

Typical Analysis

(U.S. Standard Test Sieves)

%Ash	0.1
Bulk Density lb/ft ³	6
Surface Area m ² /g	254
Tinting Strength	87
Particle Size nm	30
Dibutyl Phthalate Absorb	192

Test Methods

The PDS lists percentages which are only guaranteed following specific agreement between Asbury and the customer. They are listed here only to indicate approximate physical and chemical analysis. Purchasers should thoroughly test and independently verify satisfactory results before application. The user assumes the risk and liability for loss, damage, or injury arising from the application of the goods furnished.

UNCONTROLLED DOCUMENT: Prior to placing an order based on this PDS, contact the Asbury Sales Department to confirm that the information contained herein is current.

Revision Level: Revision 3

Revision Date:

9/14/2012

Asbury Graphite Mills, Inc.

PO Box 144 405 Old Main St.

Asbury, New Jersey 08802

Tel: (908) 537-2155 **Fax:** (908) 537-2108 **http://** www.asbury.com