RY LUBRICANTS AND SPECIALTY PRODUCTS GROUP

A division of Asbury Carbons, Inc.

Cummings-Moore Graphite Co. • 1646 N. Green Ave. • Detroit, MI 48209 Tel: (313) 841-1615 • Fax: (313) 841-4880 • www.asbury.com

PRODUCT INFORMATION

Graph-on Lubricant Sticks

В

0

Description:	Graph-on Lubricant Sticks are specially formulated high-temperature lubricant sticks designed to coat, lubricate, and reduce friction on various surfaces.	
Physical Properties: (As supplied)	Lubricating Solid Sizes Available Shelf Life	: Graphite : 2 in. diameter X 10 in. long : Indefinite
Typical Uses:	 Lubricant for tough grinding and cutting operations – reduces friction and heat while increasing equipment life. Coating for dummy blocks and billet ends in aluminum extrusion operations. Foundry mold touch-up, slide gate refractory plate lubrication, trough coating, etc. Ideal as a general-purpose lubricant for operations such as drilling, tapping, pipe cutting, etc. Allows pinpoint lubrication to avoid housekeeping problems associated with fluid or grease-type lubricants. 	
Method of Use:	Graph-on Lubricant Sticks can be applied directly to area requiring lubrication. Graph-on Sticks are designed for application on surfaces with temperatures from 400 to 850°F (204 to 454°C). Lubricant will melt onto hot surface, coat smoothly and evenly, and resist running and dripping. For lower-temperature operations, try our Dixon Lube Sticks .	
Precautions:	Use caution and employ proper personal protective equipment when working near hot surfaces and molten Lube Stick ends. Please refer to Material Safety Data Sheet for safety and first aid instructions.	

WORLD'S LARGEST PROCESSOR OF GRAPHITES AND OTHER CARBONACEOUS PRODUCTS

Information presented in this product information sheet is considered reliable, but conditions and methods of use, that are beyond our control may modify results and performance. The PDS lists percentages that are guaranteed only following specific agreement between Dixon Lubricants and Specialty Products Group and the customer. They are listed here to indicate approximate physical and chemical analysis. The user assumes the risk and liability for loss, damage or injury arising from the application of the goods furnished.